

Oracle MA-X Super High-Definition Audio Interconnect s



Engineers at MIT Cables understand that every piece of music is formed on a foundation built from the percussion and bass instruments. Our new SHD

interconnect works to control and properly interface the lowest of the bass regions. The SHD interconnect allows your system to articulate down to 10hz, well below the lowest



Selectable articulation!

note of a typical recording. This lowest region of the audio spectrum is an area not previously addressed in terms of articulation contrast. The SHD also controls the delicate ambient reflections from surrounding ceilings, walls, and stage floors in the recording venue, SHD technology can deliver the most natural, enthralling listening experience ever thought possible.

Oracle MA-X SHD interconnect, single-ended

- 110 Poles of Articulation
- Low frequency articulation on/off for tuning flexibility
- A.A.R.M. (Adjustable Articulation Response Module)
- Impedance Matching–*Switchable* up to 3 meters. Please specify Low (5-50 k Ω), Mid (40-100 k Ω) or High (90 k Ω & Up) Impedance for lengths over 4 meters.
- Patented V-Configuration for an easy install with strain relief. (Can be special ordered in a straight through Configuration)

| SKU | PRODUCT | | | QUANTITY | LENGTH | |
|----------------|---------|------|-----|----------|--------|---------------|
| ORAMA-XSHD-1 | Oracle | MA-X | SHD | 1 pr. | 1 | m (3.3 ft.) |
| ORAMA-XSHD-1.5 | " | | | 1 pr. | 1.5 | 5 m (4.9 ft.) |
| ORAMA-XSHD-2 | | | | 1 pr. | 2 | m (6.6 ft.) |
| ORAMA-XSHD-3 | | | | 1 pr. | 3 | m (10 ft.) |

Additional lengths available in 1 meter increments: Consult Price Sheet. 1/2 pairs available



Oracle MA-X SHD interconnect, balanced XLR

- 113 Poles of Articulation
- Low frequency articulation on/off for tuning flexibility
- A.A.R.M. (Adjustable Articulation Response Module)
- Impedance Matching–*Switchable* up to 3 meters. Please specify Low (5-50 k Ω), Mid (40-100 k Ω) or High (90 k Ω & Up) Impedance for lengths over 4 meters.
- Patented V-Configuration for an easy install with strain relief. (Can be special ordered in a straight through Configuration)

| SKU | PRODUCT | | | QUANTITY | TY LENGTH | | |
|-------------------|----------|--------|--------|----------|-----------|-------------|--|
| ORAMA-XSHDPRO-1 | Oracle I | MA-X S | HD XLR | 1 pr. | 1 | m (3.3 ft.) | |
| ORAMA-XSHDPRO-1.5 | | | " | 1 pr. | 1.5 | m (4.9 ft.) | |
| ORAMA-XSHDPRO-2 | | | | 1 pr. | 2 | m (6.6 ft.) | |
| ORAMA-XSHDPRO-3 | | " | " | 1 pr. | 3 | m (10 ft.) | |

Additional lengths available in 1 meter increments:

Consult Price Sheet.

1/2 pairs available



Balanced (XLR) Connectors

