## 340i X

## Integrated Amplifier



M O O N



## 340i X Integrated Amplifier

O O N

The MOON 340i X is the ultimate example of a world-class yet affordable integrated amplifier. Combining high power, sonic finesse and superb flexibility, the MOON 340i X will seduce you with its musical authority, as well as its rich, engaging and lifelike sound quality. An optional built-in MC/MM phono stage and a high-performance DAC (32-bit/384kHz + DSD) round out this compact nerve-center for your music system. Finally, balanced inputs round out plethora of connectivity options the 340i X offers.

- 6 (six) line-level inputs including a front-mounted 1/8" minijack for personal media players.
- 1 (one) pair of balanced input (XLR).
- Headphone output on 1/4" jack located on the front panel.
- A massive oversized power supply using a custom toroidal transformer design.
- "Class A" output to 5 watts for greater efficiency.
- One audio input which functions as a "pass-through", bypassing the gain stage to accommodate components like a home-theater processor, whose own volume control is used instead.
- Precision matched proprietary MOON Bipolar output transistors for improved bass response and accurate sonic reproduction.

## **Specifications**

Input Sensitivity	370 mV - 3.0 V RMS
Input impedance	11 kΩ
Output power at $8\Omega$	100W per channel
Output power at $4\Omega$	200W per channel
Crosstalk	-88 dB
Optional Digital Inputs	S/PDIF, USB, Optical
DSD sample rates	DSD64, DSD128 & DSD256
Shipping weight	28lb/13kg

Gain	37dB
Signal to Noise ratio	110dB @ full power
THD (20 Hz - 20 kHz @ 1 W)	< 0.015%
THD (20 Hz - 20 kHz @ 100 W)	< 0.05 %
Intermodulation Distortion (IMD)	< 0.03%
Maximum PCM Resolution	32-bit/384kHz
Frequency response (full range)	2Hz - 90kHz +0/-3dB
Dimensions	16.9 x 3.5 x 14.8 in
(width x height x depth)	42.9 x 8.9 x 37.6 cm



















simaudio.com

Available finishes are dependant on location