

## **VENOM-X** SPEAKER CABLES, INTERCONNECTS AND DIGITAL CABLES

VENOM-X interconnects are the finest examples yet of the innovation and science that has made Shunyata Research products the most heralded of their kind. Designer Caelin Gabriel's goal was to create a series of affordable products with build quality, performance and technology advantages missing from even the most expensive designs. Within the VENOM-X range of cables, Shunyata Research has applied its most consequential conductor refinements, including PMZ (Precision Matched conductor) technology, VTX<sup>™</sup> conductors, and premium fluorocarbon dielectrics. Based on exhaustive test results, the VENOM-X range of cables have exceeded every expectation. VENOM-X cable designs offer performance and build quality previously considered unobtainable at two to three times their affordable price points.



### SHUNYATA RESEARCH

shunyata.com

#### GIANT STEPS

The key to the VENOM-X cables performance is their customization, conductor treatments and the foundation of science that underscores all Shunyata Research cable designs. Whether it is the PMZ conductors in the digital cables that eliminates added impedance, or the balanced tone and geometry of VTX<sup>TM</sup> conductors in the speaker cables, the VENOM-X model cables are poised to become Shunyata's next range of multi-award-winning products.

### THE SOUND OF VENOM-X

What do VENOM-X cable designs sound like? Using live music as a guide, VENOM-X model speaker cables, digital cables and interconnects convey the immediacy, dynamics and propulsion that we might experience at a live event. VENOM-X cables also perform with a beautifully refined voice that is impossible to find anywhere near their reasonable prices. VENOM-X cables convey an inherent sense of transparency, accurate timing and low-level detail that simply does not exist even in some of the world's most expensive cables.

#### APPLICATIONS

An integrated VENOM-X system of cables will deliver performance that rivals any other SOTA cable system - often at less than one-quarter of the cost. VENOM-X cables are specifically designed to deliver jaw-dropping performance in systems of all types, whether solid-state, digital, tube and analog. Even right out of the box, one listen to the VENOM-X interconnects, speaker cables and digital cables will convince even the most hardened skeptics of their inherent design pedigree and performance.









# VENOM-X SP

Conductors	8 Gauge VTX™
Dielectric	PTFE
Connectors	STIS v3
KPIP <sup>™</sup> Processing	4-days
Standard Length	2.00 meters

# VENOM-X XLR

Conductors	Silver-copper alloy
Dielectric	PTFE
Connectors Platinum Plated Copper	
<b>KPIP™ Processing</b> 4-days	
Standard Lengt	h 1.00 meters

Conductors	Silver-copper alloy		
Dielectric PTFE			
Connectors Platinum Plated Copper			
KPIP™ Processing 4-days			
Standard Leng	th 1.00 meters		

**VENOM-X RCA** 



VENOM-X RCA PHONO

Conductors	Silver-copper alloy		
Dielectric	PTFE		
Connectors Platinum Plated Copper			
Ground Wire	Venom CGC		
KPIP <sup>™</sup> Processi	ing 4-days		
Standard Leng	th 1.00 meters		



## VENOM-X S/PDIF

Conductors	PMZ	
Dielectric	PTFE	
Connectors Platinum Plated Copper		
Impedance	75 ohms	
KPIP <sup>™</sup> Processing	4-days	
Standard Length	1.00 meters	



# VENOM-X CLOCK-75

Conductors	PMZ
Dielectric	PTFE
Connectors Platinum Plated Copper	
Impedance	75 ohms
KPIP <sup>™</sup> Processing	4-days
Standard Length	1.00 meters



# VENOM-X AES/EBU

Conductors		PMZ
Dielectric		PTFE
Connectors	Platinum	Plated Copper
Characteristic Imp	edance	100-110 ohms
KPIP <sup>™</sup> Processing		4-days
Standard Length		1.00 meters



Shunyata Research digital cables are produced using a **Precision Matched Impedance** cable geometry — PMZ. This means that tolerances of the conductor surface, dielectric extrusion, and the precision of the braided shield are held to minute variances. To

achieve tight tolerances, extrusion and braiding machines must be run at one-quarter speed during manufacturing. Better performance is achieved through a reduction of cable-induced signal jitter.

- Definition: Z = impedance



Kinetic Phase Inversion Processing<sup>™</sup> was developed by Caelin Gabriel after years of research into the underlying causes of various effects such as burn-in, wire directionality and the effects of cryogenic treatment. He discovered that there was an underlying

core principle that burn-in and cryogenics only partially addressed. Once the governing principle was understood it became possible to create a processor that reduces the need for long burn-in periods and eliminates the need for cryogenic treatment.



Shunyata Research's exclusive **VTX™** conductors are made in the shape of virtual tubes. The core of the conductor is completely hollow, minimizing skin effects and random eddy currents. They are produced using OFE Alloy-101.

Safety Assurance: All models

Continuity and polarity tests — by two technicians HiPOT tests insulation breakdown @ 1,200 VAC

## LIMITED LIFETIME WARRANTY

The unparalleled craftsmanship and build quality of Shunyata Research products is backed by a limited lifetime warranty. This demonstrates our commitment to building the finest products on the planet and providing exceptional customer support.

- valid only in the US and Canada -

©2022 Shunyata Research Inc.

Reproduction of this brochure and its contents, in part or whole, is strictly forbidden without prior consent from Shunyata Research. Shunyata Research reserves the right to change specifications at any time without prior notice.

## SHUNYATA RESEARCH

26273 Twelve Trees Lane, Poulsbo, Washington 98370 360 598 9935 | www.shunyata.com